

BEAL

CONSULTING ENGINEERING & PROJECT MANAGEMENT

REPORT

ENVIRONMENTAL IMPACT
MANAGEMENT SERVICES

STORM WATER MANAGEMENT PLAN AND WATER BALANCE FOR MANUNGU COLLIERY

Submitted to:

*Brian Whitfield
Block 5 Fernridge Office Park,
5 Hunter Avenue,
Ferndale,
Randburg.
2123, South Africa.*



28 September 2018

Report Number:

B196_SWMP&Water
Balance



1. CONTENTS

1. INTRODUCTION	4
1.1. Study objective	4
2. CLIMATIC DATA.....	4
3. SITE LOCATION.....	4
4. WATER BALANCE	4
4.1. Water Balance Components	5
4.2. Water Balance Description.....	5
4.3. Sources of Flow Information	5
4.4. Water Balance Results	5
5. POLLUTION CONTROL DAM SIZING.....	6
5.1. Introduction.....	6
5.2. Methodology	6
5.2.1. 50-Year and 100-Year Storm Events	6
5.2.2. Monthly Continuous Modelling	6
5.3. Results.....	7
5.4. Spillway Sizing.....	8
6. STORM WATER CHANNEL SIZING	8
6.1. Catchment Delineation.....	8
6.2. Peak Rainfall.....	8
6.3. Flood Peak Calculation	8
6.4. Channel and Berm Specifications	8
6.5. Channel Sizing.....	8
6.6. Channel 1 upgrade	9
7. CONCLUSIONS.....	11
8. REFERENCES	11

LIST OF TABLES

Table 1: Climate data	4
Table 2: Peak 24-hr rainfall depth for the Manungu Colliery	6
Table 3: Curve numbers used for the SCS storm water calculations	6
Table 4: Inputs and outputs modelled	6
Table 5: Required PCD capacities	7
Table 6: Spillway sizing	8
Table 7: Summary of infrastructure sizes	10

LIST OF APPENDICES

Appendix A: Water Balance Diagrams

Appendix B: Storm Water Management Drawings

1. INTRODUCTION

Environmental Impact Management Services (EIMS) commissioned BEAL Consulting and Project Management (Pty) Ltd to calculate a water balance for the Manungu Colliery and to size the storm water management infrastructure. This report provides the water balance and infrastructure results for the study as well as recommendations resulting from the work done.

1.1. Study objective

The project objectives are as follows:

- Calculate a desktop water balance for the proposed colliery.
- Size the pollution control dam and spillway.
- Size the clean and dirty storm water channels that are proposed to control storm water on and around the site.

2. CLIMATIC DATA

The climate data used in this study is summarised in Table 1.

Table 1: Climate data

Month	Average rainfall (mm)	Average evaporation (mm – S-Pan)
January	119.3	184
February	95.5	154
March	86.0	152
April	41.2	117
May	18.4	98
June	6.1	80
July	5.9	87
August	8.3	116
September	22.4	150
October	67.5	181
November	101.1	171
December	106.9	188
Total	678*	1 677

* Note: The mean annual precipitation does not necessarily equal the sum of the monthly average precipitation.

3. SITE LOCATION

Manungu Colliery is located approximately 10 km south of Delmas. The site is located in quaternary catchment B20A, in the Olifants River catchment.

4. WATER BALANCE

The water balance presented in this report is a static water balance. It represents average flows between facilities and along hydrological interfaces. Being a static water balance showing average flows, peak flows cannot be accounted for.

The Mpumalanga Highveld has distinct wet and dry seasons. Over 91% of Manungu Colliery's mean annual rainfall falls between September and April inclusively. Over 77% of the area's

mean annual evaporation occurs in this period. For this reason, the water balance was divided into a wet season and a dry season water balance. The wet season water balance represents the period 1 September to 30 April. The rest of the year is included in the dry season water balance. The two seasonal water balances are combined into an annual water balance, presented in Appendix A.

4.1. *Water Balance Components*

The water balance on the proposed Manungu Colliery is made up of the contractors camp, product and ROM stockpiles, pollution control dams (PCDs), offices, various overburden stockpiles, and undeveloped areas between this infrastructure.

4.2. *Water Balance Description*

Two water balances are presented – one that represents the current infrastructure layout and one that represents a future infrastructure layout.

The average wet and dry season water balances for the proposed Manungu Colliery are provided in Appendix A. The inflows are presented on the left of the water balance figures. The facilities and inter-facility flows are shown in the centre of the water balance figures. The outflows are shown on the right of these figures.

The direction of water movement is illustrated with black arrows. The values adjacent to the arrows represent average flows in m³/day. Clean water flows are shown in blue, while dirty flows are shown in red.

One of the fundamental principles of a water balance is that inflows must equal outflows unless the difference is accommodated in storage changes. The pollution control dams are relatively small and will not accommodate storage changes over a season so storage changes are assumed to be zero.

4.3. *Sources of Flow Information*

Daily rainfall data was sourced from the CCWR (Computing Centre for Water Research, Natal University) rainfall database (gauge number 0477309 – Delmas). The gauge is located approximately 10 km north of the site. Evaporation data and its monthly distribution were sourced from the Water Resources of South Africa Study data set, zone 4A (Midgley et al., 1990). Runoff factors were informed by average runoff for the quaternary catchments B20A, documented in the Water Resources of South Africa Study report (Middleton et al., 2009). Peak rainfall was statistically calculated from the rainfall data.

Groundwater volumes are based on recorded pit outflows. Potable water and dust suppression volumes are based on recorded data. A groundwater study has been commissioned by the client to confirm the groundwater inflows into the pit. Groundwater modelling results were not available at the time of writing. The water balance assumptions should be revisited once additional reliable data becomes available.

4.4. *Water Balance Results*

The average annual water balances for the proposed Manungu Colliery are provided in Appendix A. A static water balance cannot account for the dynamics of mine development. A snapshot of the colliery's development is used to calculate the water balance. The snapshot comprises the pit development depicted in survey data provided in April 2018, as well as full pit development.

5. POLLUTION CONTROL DAM SIZING

5.1. Introduction

The pollution control dam accommodates storm water from the dirty areas on the colliery: the ROM stockpile area, the hards dump and surrounding undeveloped catchments.

5.2. Methodology

The dam sizing methodology was based on two methods:

1. the required storage resulting from a long term monthly time step water balance, plus the 50-year storm runoff volume. This is to address the requirements set out in Government Notice 704 of the South African National Water Act (GN704).
2. the normal operating volume, plus the 50-year design storm runoff. This is outlined in the GN704 implementation guidelines.

In the GN704 simulations, the 50-year storm was added to the long term monthly time series because individual storms during the month are not modelled and are averaged out during the month. This also aligns it well with the GN704 implementation guidelines.

5.2.1. 50-Year and 100-Year Storm Events

The peak rainfall data used is presented in Table 2.

Table 2: Peak 24-hr rainfall depth for the Manungu Colliery

Recurrence interval	24-hr rainfall depth (mm)
50-yr	116
100-yr	126

Peak storm water discharge was calculated using the SCS runoff equations (Schmidt and Schulze, 1987). The curve numbers used in the calculations are presented in Table 3.

Table 3: Curve numbers used for the SCS storm water calculations

Pollution control Dam	Curve Number (CN)
Roads and compacted areas	88
Dumps and stockpiles	65
Undeveloped catchments	65

5.2.2. Monthly Continuous Modelling

Monthly rainfall data from the CCWR's database (gauge number 0477309) was used in the long term water balance modelling. The modelling incorporated the inputs and outputs shown in Table 4.

Table 4: Inputs and outputs modelled

Inputs	Outputs
Direct rainfall on the dam	Evaporation losses
Storm water generated by the upstream catchment	Recycling to satisfy dust suppression
Process water flows to the PCD	

Storm water generated from the catchment was calculated on a non-linear relationship between monthly rainfall and runoff. This is presented in Appendix B. No antecedent moisture conditions were accounted for. Water reuse from the pollution control dam is based on the water balance presented in Appendix A.

5.3. Results

The mine's water balance is a positive water balance so an evaporative PCD is unfeasible. The minimum size of the PCD is the 50-year design storm volume from the PCD's catchment. However, this minimum capacity will provide no operational storage and the PCD will have to be operated empty. This is not how the mine will operate the PCDs and some operational storage will be required.

The required PCD capacities are summarised in Table 5. Note that the PCD capacities assume that the mine water balance is brought back to a neutral or deficit water balance. This can be achieved by a large continuous demand such as a water treatment plant or a washing plant.

The size of the water treatment plant will depend on the groundwater inflows into the pit. The groundwater inflows are not known at the time of writing.

Table 5: Required PCD capacities

PCD	Required capacity (m ³)
PCD 1	46 000 m ³ *
PCD 2	18 000 m ³
PCD 3	5 500 m ³
PCD 4	4 000 m ³

* Existing capacity

PCD 1

It is also important to note that the PCD 1 catchment will get smaller as the opencast mining expands. Currently, much of the PCD 1 catchment is made up of land that will be mined. This means that the design storm volume for PCD 1 will decrease over time, as its catchment is converted into an opencast pit.

Given this reality, it is deemed appropriate to provide limited operational storage currently. As the PCD 1 catchment reduces, the 50-year design storm volume decreases and operational storage increases. The capacity of PCD 1 is fixed, so storm volume is effectively converted to operational volume.

PCD 1 currently exists and is slightly too small. The 50-year storm volume is approximately 51 000 m³. To avoid having to increase its capacity, additional capacity is added to PCD 2. Pumping infrastructure must therefore be put in place to transfer water from PCD 1 to PCD 2. The capacity shortfall (5 000 m³) must be able to be transferred in 24 hours, i.e. 210 m³/hr.

PCD 2

PCD 2 has a 50-year storm volume of 3 000 m³. The PCD 1 shortfall is 5 000 m³. This must be added to the PCD 2 capacity. The mine also needs some operational storage, so an additional 10 000 m³ (operational storage allowed for) of storage must also be added to PCD 2. The required capacity for PCD 2 is therefore 18 000 m³.

PCD 3 and PCD 4

PCD 3 will only be constructed once the underground operations are constructed. The capacity of these dams cannot currently contribute to the operational storage. The required capacity of these two PCDs are limited to their 50-year design storm volumes. It is assumed that all water that accumulates in them can be pumped to the underground workings within 24 hours. The PCDs are therefore operated dry.

5.4. Spillway Sizing

The spillway on the pollution control dam will need to cater for storm water generated from the dirty upstream catchments, plus direct rainfall on the dam. This is shown in Table 6.

Table 6: Spillway sizing

Dam	100-yr flood peak	Spillway width	100-yr flow depth
PCD 1	12.8 m ³ /s	16 m	0.63 m
PCD 2	1.3 m ³ /s	3 m	0.42 m
PCD 3	2.1 m ³ /s	5 m	0.41 m
PCD 4	2.6 m ³ /s	6 m	0.42 m

6. STORM WATER CHANNEL SIZING

Clean and dirty storm water channels have been identified by BEAL. These channels, shown in the drawings presented in Appendix B, were sized during this study.

6.1. Catchment Delineation

The catchments were delineated using 0.5 m contour data supplied by Manungu.

6.2. Peak Rainfall

The peak rainfall data, presented in Table 2 was used to calculate the flood peaks.

6.3. Flood Peak Calculation

The positions of the storm water channels are shown in **Appendix B**. The sub-catchments reporting to these channels were delineated. The sub-catchments are small and the rational method is therefore a suitable method of determining the flood peaks. The old Department of Water Affairs' calculation sheet was used to determine the runoff coefficients. The time-to-concentration of the sub-catchments was calculated using the SCS method which is suitable for relatively undeveloped catchments. Adamson's TR102 (Adamson, 1981) was used to convert the 24-hour peak rainfall data to rainfall intensities appropriate to the time-to-concentration of the catchments. The 1085 method was used to calculate catchment slopes. The results of these calculations for all sub-catchments are summarised in Table 7.

6.4. Channel and Berm Specifications

Dirty channels are specified as concrete-lined channels.

Berms should be compacted and vegetated. A geotechnical investigation of the soils should be undertaken to confirm the compaction specifications.

6.5. Channel Sizing

The channels were sized to accommodate the flood peaks presented in Table 7. The Mannings open channel flow equation was used to calculate flow depth in the channel. A

Mannings n of 0.027 was used for unlined channels and 0.015 for concrete lined channels. The channels are sized assuming trapezoidal channels with side slopes of 1:1.5 (V:H).

It is good practice to allow approximately 0.3 m of freeboard in the channel. This is to allow for wave action and flow surges in the channel. A summary of the channel sizes is presented in Table 7.

6.6. Channel 1 upgrade

Channel 1 is an existing concrete-lined channel.

Table 7: Summary of infrastructure sizes

Channel	50-yr flood peak (m ³ /s)	Lining	Bottom width (m)	Longitudinal slopes (V:H)*	Max flow depth (m)	Channel depth (m)	Max flow velocity (m/s)*	Flow type at max velocity
Channel 1	8.4	Concrete	1.0	1:74	0.82	1.1	4.6	Supercritical
Channel 2	0.1	Concrete	1.0	1:200	0.36	0.6	1.8	Supercritical
Channel 3	0.3	Concrete	1.0	1:200	0.18	0.5	1.3	Supercritical
Channel 4	1.3	Concrete	1.0	1:200	0.41	0.7	2.0	Supercritical
Channel 5	0.7	Concrete	1.0	1:125	0.26	0.5	1.9	Supercritical
Channel 6	1.0	Concrete	1.0	1:62	0.26	0.5	2.8	Supercritical
Channel 7	0.2	Concrete	1.0	1:47	0.1	0.5	1.8	Supercritical

Berm	50-yr flood peak (m ³ /s)	Lining	Top width (m)	Longitudinal slopes (V:H)*	Max flow depth (m)	Berm Height (m)	Max flow velocity (m/s)*	Flow type at max velocity
Berm 1	1.3	Unlined	0.5	1:200	0.25	0.5	0.7	Subcritical
Berm 2	1.5	Unlined	0.5	1:80	0.18	0.5	0.9	Subcritical

Culvert	50-yr flood peak (m ³ /s)	Type	Span (m)	Height (V:H)*	Diameter (m)	No of
Culvert 1	negligible	Round			0.3	1
Culvert 2	negligible	Round			0.3	1
Culvert 3	0.3	Portal	1200	450		1
Culvert 4	1.3	Portal	1500	600		1
Culvert 5	0.7	Portal	1200	450		1

General note: All channels are trapezoidal with side slopes of 1:1.5 (V:H)

* Note: Flow velocities are based on the maximum longitudinal gradient. These gradients will need to be confirmed during subsequent design phases.

7. CONCLUSIONS

The water balances were calculated for current and end of life and are presented in Appendix A.

The water balances highlighted the following key results:


- The water balance appears to currently be positive during the wet season. During the dry season, dust suppression demands are likely to exceed available water.
- As the pit development increases, the water balance could become more positive during the wet season with maximum dust suppression demands being less than groundwater and storm water availability. This must be monitored.

The water balance conducted in this study is a high-level desktop water balance, providing high-level water balance outputs.

The storm water management infrastructure was sized to comply with GN704 and is presented in Appendix B.

8. REFERENCES

- Middleton, B.J. and Bailey, A.K., Water Resources of South Africa, 2005 study (WR2005), 2009. WRC Report No TT 382/08.
- Midgley, D.C., Pitman, W.V., Middleton, B.J. Surface Water Resources of South Africa, 1990. WRC Report No 298/2.1/94, Volume 2.



Dr Bruce Randell (Pr. Eng.)
Water Resources Engineer



Johann Le Roux
Operational Director


APPENDIX A
WATER BALANCE DIAGRAMS

APPENDIX B
STORM WATER MANAGEMENT DRAWINGS

Appendix A Rev 0
Daily Average: m³/yr

Manungu Colliery
Water balance

Annual
Current infrastructure
Rev 0



Total Inflows
1,318,550

Total Outflows
1,318,550

Prepared by
BEAL

Legend

- 000 Dirty Flow (m³/day)
- 000 Clean Flow (m³/day)


Note: These flows are rounded to zero decimal places for clarity. Consequently some flows may appear out of balance.

* Note: Groundwater inflows are calibrated on recorded water volumes pumped out of the pit.

Appendix A Rev 0
Daily Average: m³/yr

Manungu Colliery
Summary water balance

Annual
Current infrastructure
Rev 0





Prepared by
BEAL

Legend

- 000 Dirty Flow (m³/day)
- 000 Clean Flow (m³/day)

Note: These flows are rounded to zero decimal places for clarity. Consequently some flows may appear out of balance.

* Note: Groundwater inflows are calibrated on recorded water volumes pumped out of the pit.



TSHEDZA MINING (PTY) LTD



CONCEPTUAL STORM WATER MANAGEMENT DESIGN FOR MANUNGU COLLIERY BOOK OF DRAWINGS



**OFFICE: PRETORIA
TIJGERVALLEI OFFICE PARK BUILDING 98
UNIT 9/10 SILVERLAKES RD HAZELDEAN**

**Tel. (012) 809 4383
Fax. (086) 537 5828**


SEPT 2018

Project No :B196



TSHEDZA MINING (PTY) LTD CONCEPTUAL STORM WATER MANAGEMENT DESIGN FOR MANUNGU COLLIERY



LOCALITY MAP





LIST OF DRAWINGS	
SHEET NUMBER	SHEET TITLE
000	LOCALITY MAP AND LIST OF DRAWINGS
001	EXISTING INFRASTRUCTURE LAYOUT DRAWING
002	PROPOSED NEW INFRASTRUCTURE LAYOUT
003	STORM WATER MANAGEMENT LAYOUT PLAN
004	OPENCAST CONTRACTORS CAMP POLLUTION CONTROL DAM LAYOUT AND DETAILS
005	OPENCAST CONTRACTORS CAMP STORM WATER INFRASTRUCTURE LAYOUT DRAWINGS
006	NORTH WESTERN UNDERGROUND POLLUTION CONTROL DAM LAYOUT AND DETAILS
007	NORTH WESTERN UNDERGROUND STORM WATER INFRASTRUCTURE LAYOUT DRAWINGS
008	PLANT AREA - EXISTING AND PROPOSED NEW STORM WATER INFRASTRUCTURE LAYOUT DRAWING
009	HARDS STOCKPILE POLLUTION CONTROL DAM AND STORM WATER MANAGEMENT LAYOUT AND DETAILS

CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY



								INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT. UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT. © BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.		BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE		Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za		TSHEDZA MINING (PTY) LTD PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN DRAWING TITLE LOCALITY MAP								
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY							MVDW	RDB	RDB	BR	BR	09/21	LEAD PROJECT DRAFTER	PROJECT MANAGER	SCALE	SHEET SIZE	PROJECT No	DOC No	DOC TYPE	DRAWING No	REVISION
	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE	MVDW	RDB	N.T.S	A1	B196	000	CONC	000	00						




DIRTY WATER SYSTEM - KEY PLAN



PCD 2 - SECTION 1




PCD 2 - SECTION 2




DIRTY WATER CHANNEL 2


LINER BARRIER CONFIGURATION




PCD 2 EMBANKMENT CONFIGURATION




PCD 2 EMERGENCY SPILLWAY PLAN VIEW




PCD 2 EMERGENCY SPILLWAY - SECTION



POLLUTION CONTROL DAM - KEY PLAN



CRAWL NET DETAIL



LIFE BOUY DETAIL

CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY

REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY	MVDW	RDB	RDB	BR	BR	09/21


INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.
C) BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.

BEAL
CONSULTING ENGINEERS & PROJECT MANAGEMENT


Tjigervalei office park
Building 98 unit 9/10
Silverlakes rd
Hazeldean
Pretoria
<http://www.beal.co.za>

LEAD PROJECT DRAFTER: MVDW
PROJECT MANAGER: RDB
SCALE: N.T.S
SHEET SIZE: A1


CLIENT	TSHEDZA MINING (Pty) Ltd.			
PROJECT	CONCEPTUAL STORM WATER MANAGEMENT DESIGN			
DRAWING TITLE	HARDS STOCKPILE AREA POLLUTION CONTROL DAM AND STORM WATER MANAGEMENT LAYOUT AND DETAILS			
PROJECT No	DOC No	DOC TYPE	DRAWING No	REVISION
B196	001	CONC	009	00




DIRTY WATER SYSTEM - KEY PLAN




DIRTY WATER BERM 1




OPTION 1: PROPOSED UPGRADE FOR EXISTING DIRTY WATER CHANNEL 1




DIRTY WATER CULVERT STRUCTURE 6-SECTION A-A



OPTION 2: REINFORCED CONCRETE WALL NEXT TO EXISTING DIRTY WATER CHANNEL 1




DIRTY WATER CULVERT STRUCTURE 6-SECTION B-B



DIRTY WATER CULVERT STRUCTURE 6-PLAN VIEW

**CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY**

<p>INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.</p> <p>UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.</p> <p>© BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.</p>										<p>BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE</p>		<p>Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za</p>		<p>CLIENT TSHEDZA MINING (Pty) Ltd.</p>		<p>PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN</p>		<p>DRAWING TITLE PLANT AREA - EXISTING AND PROPOSED NEW STORM WATER INFRASTRUCTURE LAYOUT DRAWING</p>	
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY	MVDW	RDB	RDB	BR	BR	09/21	LEAD PROJECT DRAFTER	PROJECT MANAGER	SCALE	SHEET SIZE	PROJECT No	DOC No	DOC TYPE	DRAWING No	REVISION			
REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE	MVDW	RDB	N.T.S	A1	B196	001	CONC	008	00			



CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY

REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY	MVDW	RDB	RDB	BR	BR	09/21

INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.
© BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.

BEAL
CONSULTING ENGINEERING & PROJECT MANAGEMENT

BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD
PRETORIA OFFICE


Tijgervallei office park
Building 98 unit 9/10
Silverlakes rd
Hazeldean
Pretoria
<http://www.beal.co.za>

LEAD PROJECT DRAFTER: MVDW
PROJECT MANAGER: RDB
SCALE: N.T.S
SHEET SIZE: A1

CLIENT: 18° 0' E	TSHEDZA MINING (Pty) Ltd.			
PROJECT	CONCEPTUAL STORM WATER MANAGEMENT DESIGN			
DRAWING TITLE	EXISTING INFRASTRUCTURE LAYOUT DRAWING			
PROJECT No	DOC No	DOC TYPE	DRAWING No	REVISION
B196	001	CONC	001	00




POLLUTION CONTROL DAM - KEY PLAN




PCD 4 EMBANKMENT CONFIGURATION


- NOTES:**
1. ALL WORKS TO BE DONE TO SABS STANDARD.
 2. 70KG SAND FILLED UV RESISTANT BALLAST BAGS PLACED ON 5M GRID SPACING ON PCD FLOORS.
 3. THE PCD HAS A NO OPERATIONAL STORAGE AND IS ASSUMED TO BE OPERATED EMPTY.
 4. THE PCD HAS A 4000M³ CAPACITY THAT WILL ACCOMMODATE THE 50 YEAR STORM VOLUME.
 5. THE PCD HAS A 0.8M FREEBOARD AND A CREST WIDTH OF 3M.




LINER BARRIER CONFIGURATION




PCD 4 EMERGENCY SPILLWAY - PLAN VIEW




PCD 4 EMERGENCY SPILLWAY - SECTION




PCD 4 - SECTION 1



PCD 4 - SECTION 2





CRAWL NET DETAIL




LIFE BOUY DETAIL

**CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY**


INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.									Tjgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za		CLIENT TSHEDZA MINING (Pty) Ltd.								
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.									BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE		PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN								
BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.								LEAD PROJECT DRAFTER MVDW		PROJECT MANAGER RDB		SCALE N.T.S		SHEET SIZE A1		DRAWING No 004		REVISION 00	
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY							MVDW	RDB	RDB	BR	BR	09/21	DRAWING No 004					
REVISION	DESCRIPTION							DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE	PROJECT No B196	DOC No 001	DOC TYPE CONC	DRAWING No 004	REVISION 00	




DIRTY WATER SYSTEM - KEY PLAN




DIRTY WATER CHANNEL 7




DIRTY WATER CHANNEL 6




CLEAN AND DIRTY WATER SEPARATION BERM 2




DIRTY WATER CHANNEL 5



DIRTY WATER CULVERT STRUCTURE 5-SECTION B-B



DIRTY WATER CULVERT STRUCTURE 5-PLAN VIEW



DIRTY WATER CULVERT STRUCTURE 5-SECTION A-A

**CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY**


INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.									Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za		CLIENT TSHEDZA MINING (Pty) Ltd.							
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.									BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE		PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN							
© BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.										DRAWING TITLE OPENCAST CONTRACTORS CAMP STORM WATER INFRASTRUCTURE LAYOUT DRAWING								
00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY							MVDW	RDB	RDB	BR	BR	09/21	PROJECT No B196	DOC No 001	DOC TYPE CONC	DRAWING No 005	REVISION 00
REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE	LEAD PROJECT DRAFTER	PROJECT MANAGER	SCALE	SHEET SIZE	PROJECT No	DOC No	DOC TYPE	DRAWING No	REVISION		

29° 20' 24" E

29° 19' 12" E

29° 18' 0" E

29° 16' 48" E




CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY

29° 20' 24" E


29° 19' 12" E

29° 16' 48" E


00 CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY		MVDW	RDB	RDB	BR	BR	09/21	INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT. UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT. BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.	<p>BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE</p>	Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za	CLIENT TSHEDZA MINING (Pty) Ltd.	PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN				
REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE	LEAD PROJECT DRAFTER MVDW		PROJECT MANAGER RDB	SCALE N.T.S	SHEET SIZE A1	PROJECT No B196	DOC No 001	DOC TYPE CONC	DRAWING No 002




POLLUTION CONTROL DAM - KEY PLAN



PCD 4 - SECTION 1




PCD 3 - SECTION 2




PCD 3 EMBANKMENT CONFIGURATION

NOTES:


1. ALL WORKS TO BE DONE TO SABS STANDARD.
2. 70KG SAND FILLED UV RESISTANT BALLAST BAGS PLACED ON 5M GRID SPACING ON PCD FLOORS.
3. THE PCD HAS A NO OPERATIONAL STORAGE AND IS ASSUMED TO BE OPERATED EMPTY.
4. THE PCD HAS A 5500M³ CAPACITY THAT WILL ACCOMMODATE THE 50 YEAR STORM VOLUME.
5. THE PCD HAS A 0.8M FREEBOARD AND A CREST WIDTH OF 2M.




LINER BARRIER CONFIGURATION




PCD 3 EMERGENCY SPILLWAY - PLAN VIEW



PCD 3 EMERGENCY SPILLWAY - SECTION




LIFE BOUY DETAIL




CRAWL NET DETAIL

**CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY**


INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.								Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za		CLIENT TSHEDZA MINING (PTY) LTD	
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.								BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE		PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN	
BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.								LEAD PROJECT DRAFTER MVDW		DRAWING TITLE NORTH WESTERN POLLUTION CONTROL DAM LAYOUT AND DETAILS	
								PROJECT MANAGER RDB		PROJECT No B196	
								SCALE N.T.S		DOC No 001	
								SHEET SIZE A1		DOC TYPE CONC	
								DATE 09/21		DRAWING No 006	
								REVISION		REVISION	
								00		00	
								CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY			
								DRAWN			
								DRAWN CHECK			
								DESIGN			
								DESIGN CHECK			
								AUTHORISED			




DIRTY WATER SYSTEM - KEY PLAN




DIRTY WATER CHANNEL 3




DIRTY WATER CHANNEL 4




DIRTY WATER CULVERT STRUCTURE 3-SECTION A-A




CLEAN WATER CULVERT STRUCTURE 1 & 2-SECTION A-A




DIRTY WATER CULVERT STRUCTURE 3-PLAN VIEW




CLEAN WATER CULVERT STRUCTURE 1 & 2-PLAN VIEW




DIRTY WATER CULVERT STRUCTURE 3-SECTION B-B




CLEAN WATER CULVERT STRUCTURE 1 & 2-SECTION B-B




DIRTY WATER CULVERT STRUCTURE 4-PLAN VIEW



DIRTY WATER CULVERT STRUCTURE 4-SECTION A-A



DIRTY WATER CULVERT STRUCTURE 4-SECTION B-B



CLEAN AND DIRTY WATER SEPARATION BERM

CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY

00	CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY	MVDW	RDB	RDB	BR	BR	09/21
REVISION	DESCRIPTION	DRAWN	DRAWN CHECK	DESIGN	DESIGN CHECK	AUTHORISED	DATE



INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.
© BEAL CONSULTING ENGINEERS AND PROJECT MANAGEMENT.



BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD
PRETORIA OFFICE

Tjgervallei office park
Building 98 unit 9/10
Silverlakes rd
Hazeldean
Pretoria
http://www.beal.co.za

CLIENT	TSHEDZA MINING (PTY) LTD				
PROJECT	CONCEPTUAL STORM WATER MANAGEMENT DESIGN				
DRAWING TITLE	NORTH WESTERN UNDERGROUND STORM WATER INFRASTRUCTURE LAYOUT DRAWING				
PROJECT No	B196	DOC No	001	DOC TYPE	CONC
SHEET SIZE	A1	DRAWING No	007	REVISION	00



LEGEND

- DIRTY WATER FLOW DIRECTION
- CLEAN WATER FLOW DIRECTION
- DIRTY WATER CHANNEL
- CLEAN AND DIRTY WATER SEPARATION BERM
- CULVERT STRUCTURE
- AREA TO BE REHABILITATED
- 50 YEAR FLOOD LINE
- 100 YEAR FLOOD LINE
- ROAD

DIRTY WATER CATCHMENTS AREAS (D):

- D 1- 50 716 m²
- D 2- 21 434 m²
- D 3- 9 916 m²
- D 4- 40 387 m²
- D 5- 10 084 m²
- D 6- 180 964 m²
- D 7- 86 446 m²
- D 8- 911 032 m²
- D 9- 57 830 m²
- D 10- 103 695 m²

CLEAN WATER CATCHMENTS AREAS (C):

- C 1- 115 542 m²
- C 2- 31 483 m²
- C 3- 31 483 m²

CONCEPTUAL DESIGN
ISSUED FOR
INFORMATION ONLY

29° 20' 24" E		29° 19' 12" E		29° 18' 0" E		29° 16' 48" E	
INFORMATION CONTAINED ON THIS DRAWING IS THE COPYRIGHT OF BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT.						Tijgervallei office park Building 98 unit 9/10 Silverlakes rd Hazeldean Pretoria http://www.beal.co.za	
UNAUTHORISED USE OR REPRODUCTION OF THIS PLAN EITHER WHOLLY OR IN PART WITHOUT WRITTEN PERMISSION INFRINGES COPYRIGHT.				BEAL CONSULTING ENGINEERS & PROJECT MANAGEMENT (PTY) LTD PRETORIA OFFICE		CLIENT TSBEDZA MINING (Pty) Ltd.	
00 CONCEPTUAL DESIGN ISSUED FOR INFORMATION ONLY				MVDW RDB RDB BR BR 09/21		PROJECT CONCEPTUAL STORM WATER MANAGEMENT DESIGN	
REVISION DESCRIPTION				DRAWN DRAWN CHECK DESIGN DESIGN CHECK AUTHORISED DATE		DRAWING TITLE STORM WATER MANAGEMENT LAYOUT PLAN	
				LEAD PROJECT DRAFTER PROJECT MANAGER SCALE SHEET SIZE		PROJECT No DOC No DOC TYPE DRAWING No REVISION	
				MVDW RDB N.T.S A1		B196 001 CONC 003 00	